



(19)

(11) Publication number: **2002056839 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **2000244464**(51) Intl. Cl.: **H01M 2/30 H01M 2/02 H01M 2/26 H01M 2/34 H01M 10/40**(22) Application date: **11.08.00**

(30) Priority:

(43) Date of application
publication: **22.02.02**(84) Designated contracting
states:(71) Applicant: **NEC MOBILE ENERGY KK**(72) Inventor: **TANAKA IZUMI**

(74) Representative:



(54) SEALED BATTERY

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a laminate battery having good sealing characteristic.

SOLUTION: In this sealed battery, an outline of a projected image onto an exterior material surface of a contact part between an electrode tab connected to a battery element and guided to the outside and an flexible exterior material is formed of one line other than a straight line, and cross section of the electrode tab disposed on a sealing surface is not larger than cross section of other parts.

COPYRIGHT: (C)2002,JPO



Delphion


RESEARCH

INTEGRATED IAM

SERVICES

INSIDE DELPHION

The Delphion Integrated View


Buy Now: [More choices...](#)Tools: Add to Work File: [Create new Work File](#) VI w: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent...](#) [Email this to a friend](#)Title: **JP2002056839A2: SEALED BATTERY**Country: **JP Japan**Kind: **A2 Document Laid open to Public inspection**Inventor: **TANAKA IZUMI;**Assignee: **NEC MOBILE ENERGY KK**
[News, Profiles, Stocks and More about this company](#)Published / Filed: **Feb. 22, 2002 / Aug. 11, 2000**Application
Number: **JP2000000244464**IPC Code: **H01M 2/30; H01M 2/02; H01M 2/26; H01M 2/34; H01M 10/40;**Priority Number: **Aug. 11, 2000 JP2000000244464**

Abstract:

PROBLEM TO BE SOLVED: To provide a laminate battery having good sealing characteristic.

SOLUTION: In this sealed battery, an outline of a projected image onto an exterior material surface of a contact part between an electrode tab connected to a battery element and guided to the outside and an flexible exterior material is formed of one line other than a straight line, and cross section of the electrode tab disposed on a sealing surface is not larger than cross section of other parts.

COPYRIGHT: (C)2002,JPO

Family: **None**Other Abstract Info: **None**[View
Image](#)

1 page

[this for the Gallery...](#)[Nominate](#)